



Mini power supply 230 V

346030

Description

2 DIN module device for:

- basic video door entry systems (e.g. apartment intercom)
- mini SOUND SYSTEMS (absorption up to 600 mA).

It is a double insulation safety device.

The power supply is inside a module plastic rail enclosure, and its installation must be in accordance with the regulations of the country of use.

The device must not be configured.

Technical data

PRI (power supply input AC):

Rated voltage:	220 – 240 Vac
Rated current:	200 - 190 mA
Working voltage range:	187 – 265 V
Working frequency range:	47 – 63 Hz
Input power at full load:	21.5 W max
Dissipated power:	5.3 W (max.)
Performance at full load:	80% typ.
Power in stand by:	< 1 W
Operating temperature:	5 – 40 °C
Integrated fuse (PRI side):	F1 T2A 250V (CANNOT BE REPLACED)

SCS A-V; SCS:


Rated voltage:	27 V +/- 100 mV
Rated current:	0 – 0.6 A
Rated power:	16.2 W

Standards, Certifications, Marks

Standards: CEI EN60065 - CEI 64-8-4

Dimensional data

2 DIN modules



WARNING: THE (SCS A-V) AND (SCS) OUTPUT CANNOT BE USED AT THE SAME TIME

Legend

- 1 - 230 Vac input connection clamps 50-60 Hz
- 2 - SCS AV output connection clamps (27 V)
- 3 - SCS output connection clamps (BUS 27V)
- 4 - Operating status notification LEDs:
 - (GREEN ON) - normal operation of the power supply
 - (RED ON) - output current overload

Assembly, Installation

Comply with the following installation requirements:

- The power supply must always be installed in appropriate enclosures.
- It must be kept away from water drips and sprays.
- Do not obstruct the air vents.
- A double-pole thermal magnetic circuit breaker with contact separation of at least 3 mm must be used, positioned near the power supply. The circuit breaker is used both to disconnect the power supply from the electric network, and to protect it.