



P41S


Ophangprofielen 41 enkel

CABLOFIL

 CF 30 met CF 105
L. 50 -> 600 mm



	Belasting (DaN.m)	L (mm)	Verp.	GC	316L
P41S300	100	300	1	CM595153	-
P41S400	100	400	1	CM595163	-
P41S500	100	500	1	CM595103	CM595104
P41S600	100	600	1	CM595173	-
P41S800	100	800	1	CM595113	CM595114
P41S1000	100	1000	1	CM595123	CM595124
P41S1500	100	1500	1	CM595133	CM595134
P41S2000	100	2000	1	CM595143	CM595144



Voor kortere lengtes dan 500 mm, gebruik maken van consoles C41S en C41D als hangprofiel.
Andere lengtes op aanvraag.

Draadgoten: keuzetabel

MATERIAALSOORTEN

EZ Elektrolytisch verzinkt
Norm EN ISO 2081

GS Sendzimir verzinkt
Norm EN 10346

PG Vóór fabricage verzinkt
Norm EN 10244-2

GC Thermisch verzinkt
Norm EN ISO 1461

DC Geomet bescherming

304L RVS 304 L (Inox)
Norm EN 10088-2

316L RVS 316 L (Inox)
Norm EN 10088-2