

SPECIFICATION DATA SHEET



REF

from 042265 to 042268

TYPE

SINGLE-PHASE ENCLOSED AUTO-TRANSFORMER

RATED CHARACTERISTICS

230/400V AC or 400/230V AC by reversibility

ELECTRICAL CHARACTERISTICS

Fréquence : 50/60Hz
Class H insulation
Class I
Air-cooled product
IP 21 - IK 08

Insulation voltage : between coil and core : 3000V

Cat Number	Nominal power (VA)	No load losses (W)	Voltage drop $\cos \phi = 1$	Efficiency $\cos \phi = 1$	Ucc (%)
042265	3150	55,0	1,5%	0,97	1,7
042266	4000	66,0	0,9%	0,97	1,1
042267	6300	77,0	0,9%	0,98	1,1
042268	8000	83,0	0,3%	0,98	1,3

Transformateur in accordance with IEC 60076-11

Cat Number	Nominal power (VA)	Dimensions (mm)			Fixation (mm)			Weight (Kg)
		A	B	C	F	G	Diameter	
042265	3150	250	270	253	230	91	7	21
042266	4000	250	270	253	230	130	7	28
042267	6300	320	330	253	300	101	9	38
042268	8000	300	390	230	280	130	9	37,2

