





Certifications
Fire Resistance : EN 1366-3
Classification : EN 13501-2
ETA 13 / 0993

EZ-PATH Systems	Ø Cables (mm)	Flexible wall	Rigid wall		Rigid Floor
		≥122mm 	≥122mm 	≥150mm 	≥150mm 
1 x CM250018 + CM250240 1 x EZD33T + EZP133CWT	OD ≤ Ø 21	EI120	EI120	EI120	-
	OD ≤ Ø 50	-	-	EI60 / EI120	-
2 x CM250018 + CM250120 2 x EZD33T + EZP233WT	OD ≤ Ø 21	EI120	EI120	EI120	-
	OD ≤ Ø 50	-	-	EI60 / EI120	-
3 x CM250018 + CM250130 3 x EZD33T + EZP333WT	OD ≤ Ø 21	EI120	EI120	EI120	-
	OD ≤ Ø 50	-	-	EI60 / EI120	-
4 x CM250018 + CM250140 4 x EZD33T + EZP433WT	OD ≤ Ø 21	EI120	EI120	EI120	-
	OD ≤ Ø 50	-	-	EI60 / EI120	-
7 x CM250018 + CM250170 7 x EZD33T + EZP733WT	OD ≤ Ø 21	EI120	EI120	EI120	-
	OD ≤ Ø 50	-	-	EI60 / EI120	-
1 x CM250018 + CM250220 1 x EZD33T + EZP133KT	OD ≤ Ø 21	-	-	-	EI120

All EZ-Path systems are approved empty up to 100% fill of cables

Please refer to the corresponding Application Data Sheet and Installation Sheet for more additional information about the installation method

