



LICENCE

No. 15149

Issued to:
Applicant:
BTICINO N.V.
Industriezone
Kouterveldstraat, 11
1831 DIEGEM
Belgium

Licensee:
BTICINO N.V.
Industriezone
Kouterveldstraat, 11
1831 DIEGEM
Belgium

Product : push-button switches (for fixed installations)

Trade name(s) : BTICINO

Type(s)/model(s) : Series AXOLUTE

The product and any acceptable variation thereto is specified in the annex to this licence and the documents therein referred to.

SGS CEBEC hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard specified in annex
- an inspection of the production location according to CCA Group Operational Document CIG 021
- a certification agreement with the number 171

SGS CEBEC hereby grants the right to use the CEBEC certification mark



The CEBEC certification mark may be applied to the product as specified in this licence for the duration of the CEBEC certification agreement and under the conditions of the CEBEC certification agreement.

This licence is issued on: 28/02/2007


ir. R. Maquestiau,
Managing Director

© Only integral publication of this certificate, including the annex, is allowed

SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

Product	: push-button switches (for fixed installations)
Trade name(s)	: BTICINO
Type(s)/Model(s)	: HC4005, HC4027, HC4034, HC4036, HC4037, HC4044, HC4055, HS4005, HS4027, HS4034, HS4036, HS4037, HS4044, HS4055, HX4005, HY4005
rated voltage (Un)	: 250 V~
method of application	: flush-type
method of installation	: design A
type of terminals	: screw-type
contact opening (gap)	: normal gap

Product data - type HC4027

rated current (In)	: 16 AX
number of poles	: 1 pole
pattern no(s).	: 6
colour(s)	: aluminium
design	: 2 ways; with directional arrows and central OFF position
number of modules	: 1 module

Product data - type HS4027

rated current (In)	: 16 AX
number of poles	: 1 pole
pattern no(s).	: 6
colour(s)	: anthracite
design	: 2 ways; with directional arrows and central OFF position
number of modules	: 1 module

Product data - type HC4055

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NO
colour(s)	: aluminium
design	: 1 way; push-button with momentary contact
number of modules	: 1 module

Product data - type HS4055

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NO
colour(s)	: anthracite
design	: 1 way; push-button with momentary contact
number of modules	: 1 module

Product data - type HC4005

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NO
colour(s)	: aluminium
design	: 1 way; push-button with momentary contact
number of modules	: 1 module
construction	: axial version

Product data - type HS4005

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NO
colour(s)	: anthracite
design	: 1 way; push-button with momentary contact
number of modules	: 1 module
construction	: axial version

Product data - type HX4005

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NO
colour(s)	: aluminium
design	: 1 way; push-button with momentary contact
number of modules	: 1 module
construction	: stile version

Product data - type HY4005

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NO
colour(s)	: anthracite
design	: 1 way; push-button with momentary contact
number of modules	: 1 module
construction	: stile version

Product data - type HC4044

rated current (In)	: 10 A
number of poles	: 2 poles
pattern no(s).	: 2 NO
colour(s)	: aluminium
design	: 2 way; push-button with momentary contact
number of modules	: 1 module

Product data - type HS4044

rated current (In)	: 10 A
number of poles	: 2 poles
pattern no(s).	: 2 NO
colour(s)	: anthracite
design	: 2 way; push-button with momentary contact
number of modules	: 1 module

Product data - type HC4034

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NC
colour(s)	: aluminium
design	: 1 way; push-button with momentary contact
number of modules	: 1 module
construction	: axial version

Product data - type HS4034

rated current (In)	: 10 A
number of poles	: 1 pole
pattern no(s).	: 1 NC
colour(s)	: anthracite
design	: 1 way; push-button with momentary contact
number of modules	: 1 module
construction	: axial version

Product data - type HC4036

rated current (In)	: 10 A
number of poles	: 2 poles
pattern no(s).	: 1 NO+1 NO
colour(s)	: aluminium
design	: 2 way; push-button with momentary contact
number of modules	: 1 module

Product data - type HS4036

rated current (In)	: 10 A
number of poles	: 2 poles
pattern no(s).	: 1 NO+1 NO
colour(s)	: anthracite
design	: 2 way; push-button with momentary contact
number of modules	: 1 module

Product data - type HC4037

rated current (In)	: 10 A
number of poles	: 2 poles
pattern no(s).	: 1 NO+1 NO
colour(s)	: aluminium
design	: 2 way; push-button with momentary contact and interlock
number of modules	: 1 module

Product data - type HS4037

rated current (In)	: 10 A
number of poles	: 2 poles
pattern no(s).	: 1 NO+1 NO
colour(s)	: anthracite
design	: 2 way; push-button with momentary contact and interlock
number of modules	: 1 module

TESTS**Test requirements**

NBN EN 60669-1:1996 + A1:1997 + A29:1998

Test results

The test results are laid down in certification file ref.578370/03

Remarks

This certificate is based on certificate ref. CB IT-4672 and test report(s) ref. 02AF00231/A-1/A-2/A-3/A and 02AF00232/A-1/A-2/A-3/A

Conclusion

The examination proved that all test requirements were met.

Checked by, project leader : Philippe Vankerkhove

Department Manager,
Product Certification

Certification Manager

2007-03-02 2007/03/01

2007.03.02

FACTORY LOCATION(S)

BTicino S.p.A.
Viale Borri, 231
21100 VARESE
Italy

